

TOP COAT DECORATIVE PRODUCT WITH GLITTER



DESCRIPTION

GLITTER DECORATIVE FINISH is an acrylic emulsion based, decorative finishing paint that can be applied on decorative products in the consistency of decorative paste, paint and paste, creating a metallic and reflective pearlescent appearance.

APPLICATION AREA

It is applied as a finishing material on decorative products applied after floor preparation on walls, plasters, gross concretes and wooden surfaces.

SURFACE PREPARATION

After all kinds of dirt, oil, bloated paints and dust are cleaned from the surfaces it will be applied on, surface defects should be smoothed with SAN DECO ACRYLIC PUTTY INTERIOR and primed with SAN DECO DECOPRIMER.

FEATURES

- It gives a silvery appearance to the product to which it is applied.
- It is easy to apply, does not change the texture and pattern of the product on which it is applied.
- It can be wiped off.
- Due to the strong water vapor permeability, it allows vapor to be released outside and the surface to breathe.
- It does not harm human health and environment as it is water-based.
- It allows environments of application to smell nice due to its perfume characteristic.

The Product

Composition	Acrylic Based
Density	1.03 g/cm ³
	8,59 lbs./gallon
Storage Temperature	5 °C + 35 °C 41 °F + 95 °F
Emission Limits of Volatile Organic Compounds (VOC) According to Directive 2004/42/CE	Subcategory: L VOC: 47 g/l (max); Limit Phase : 200 g/l
Theoretical Coverage (Single Coat)	610 – 814 sq. Ft/gallon
	15 – 20 m ² /L
Weight Per Gallon	8,59 lbs.
Packaging	1 Quart

The Application

Dilution	Ready To Use
Surface Preparation	San Deco Acrylic Putty Interior
Primer	San Deco Decoprimer
Application Tools	Roller, Brush, Trowel
Touch Dry Time	2-3 Hours
Complete Dry Time	24 Hours
Dry Time Temperature	23 °C/73.4°F (relative humidity at 50%)
Application Temperature (24 hours during and after the application)	5 °C + 35 °C 41 °F + 95 °F

APPLICATION INSTRUCTION

- GLITTER DECORATIVE FINISH is recommended to be applied with a special brush on decorative products with the consistency of decorative paste and other pastes without being diluted.
- GLITTER DECORATIVE FINISH is applied to the surface in one layer by being mixed homogenously with the addition of 30-40% clean water with a roller or trowel onto paint-like products.
- It should be paid attention that the ambient temperature should be minimum +5°C/41 °F, and maximum +35°C/95 °F within 24 hours during and after the application.

DRYING TIME

At 23°C/73.4°F, the touching time is 2-3 hours and the complete drying time is 24 hours.

THEORETICAL CONSUMPTION

Consumptions may vary depending on surface smoothness, absorbency and application techniques and the product to be applied on the bottom surface. Theoretical consumption in single-layer application;

-15 - 20 m² with 1 lt.

-15 - 20 m² area is painted with 1 kg.

- Paint consumption for an area of 1 m² is 50 – 65 ml and 50– 65 gr.

STORAGE

It can be stored in its unopened package, cool and dry environments, protected from direct sunlight at between +5°C/41 °F and +35°C/95 °F.



HAZARD STATEMENTS

- H317 May cause an allergic skin reaction

PRECAUTIONARY STATEMENTS

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1) May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP. 028.US - Rev01 January 2022

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 27001, ISO 45001.